

# Geoflex model GFXX-120WW-4 Fluid-to-Fluid Heat Pump & Chiller Specifications

Geoflex, Multi-flex Systems have been designed to allow for the stacking/ganging of 2, 3, 4 or more heat pump / chiller systems, offering the benefits of built-in redundancy, maintenance without complete shut-down, unparalleled operating efficiency and unloading characteristics. The stacking/ganging of systems allows increased capacity without increasing the very small footprint of the equipment. The individual components will go into most elevators fit through most doors, eliminating the need for door widening, taking out walls or cranes in high rise buildings.

The Multi-flex design offers built-in system redundancy for servicing and higher operating efficiency by staging the systems, accordingly to the load. The fluid inlets and outlets are staggered both vertically and horizontally to simplify piping connections to the heat pumps / chiller. Service panels surround the system, however, the Multi-flex systems are designed for complete service access by removing the front panel.

The electrical and performance specifications are provide for a unit with a single compressor. If the units are stacked the performance and electrical specifications must be doubled. Fluid-to-fluid heat pump / chiller systems should be designed to operate at fluid temperatures lower than 120 F (50 C). Specifying operating temperatures higher than this will result in less efficient operation and can shorten the longevity of the compressor. Units must be operating within specified operating ranges.

## GF1-120-WW-4 Performance Specifications - R410

Evaporator						Condenser						Heating & Cooling Capacity													
EFT		LFT		Flow		PD		EFT		LFT		Flow		PD		Heating Capacity		COP <sub>h</sub>	Chilling Capacity		COP <sub>c</sub>	EER	kW		
°F	°C	°F	°C	GPM	L/S	ft/h	kPa	psi	°F	°C	°F	°C	GPM	L/S	ft/h	kPa	psi		MBH	(/kW)				MBH	(/kW)
53.6	12.0	46.0	7.8	25.3	1.6	14.2	42.7	6.2	77.0	25.0	86.4	30.2	25.3	1.6	12.0	36.0	5.2	115.9	34.0	5.4	94.3	27.6	4.4	14.9	6.3
32.0	0.0	27.3	-2.6	25.3	1.6	16.0	47.9	6.9	104.0	40.0	111.0	43.9	25.3	1.6	10.7	32.0	4.6	86.8	25.4	3.0	57.4	16.8	2.0	6.7	8.6
53.5	11.9	45.3	7.4	25.3	1.6	14.3	42.8	6.2	59.0	15.0	68.6	20.3	25.3	1.6	13.2	39.5	5.7	118.6	34.7	6.8	101.2	29.7	5.8	19.9	5.1
50.0	10.0	43.7	6.5	25.3	1.6	14.5	43.4	6.3	104.0	40.0	112.7	44.8	25.3	1.6	10.6	31.9	4.6	107.3	31.5	3.6	77.5	22.7	2.6	8.9	8.7
53.6	12.0	46.3	7.9	25.3	1.6	14.2	42.7	6.2	86.0	30.0	95.3	35.2	25.3	1.6	11.5	34.5	5.0	114.5	33.6	4.8	90.5	26.5	3.8	12.8	7.0
68.0	20.0	59.8	15.4	25.3	1.6	13.2	39.5	5.7	104.0	40.0	114.7	45.9	25.3	1.6	10.6	31.7	4.6	131.4	38.5	4.3	101.0	29.6	3.3	11.4	8.9
50.0	10.0	43.0	6.1	25.3	1.6	14.5	43.5	6.3	85.0	29.4	93.9	34.4	25.3	1.6	11.6	34.7	5.0	109.8	32.2	4.6	86.2	25.3	3.6	12.4	6.9
68.0	20.0	59.0	15.0	25.3	1.6	13.2	39.6	5.7	86.0	30.0	97.0	36.1	25.3	1.6	11.4	34.3	5.0	135.7	39.8	5.5	111.1	32.6	4.5	15.4	7.2
10.0	-12.2	6.5	-14.2	25.3	1.6	18.1	54.2	7.8	85.0	29.4	90.3	32.4	25.3	1.6	11.7	35.0	5.0	65.2	19.1	2.9	42.9	12.6	1.9	6.5	6.5
15.0	-9.4	11.1	-11.6	25.3	1.6	17.6	52.7	7.6	85.0	29.4	90.7	32.6	25.3	1.6	11.6	34.9	5.0	70.1	20.5	3.1	47.6	13.9	2.1	7.2	6.6



\* Outputs and Efficiency Ratings are based on a 25% methanol and water mixture, which will increase or decrease based on anti-freeze levels  
 \*\* Pressure drop is shown in feet of head, using 25% methanol & water as the test fluid. Multipliers for other fluids are as follows:  
 - water: 0.85  
 - 30% ethanol: 1.17  
 - 35% propylene glycol: 1.23

## GF1-120WW-4 Electrical Specifications - R410A

Voltage/Phase/Hz	Compressor		Min. Circuit Ampacity	Max. Fuse Breaker Size
	RLA	LRA		
200-230/3/60	33.6	225.0	47.0	50
460/3/60	18.6	114.0	26.0	30
575/3/60	13.6	80.0	19.0	20

Note: Pumps or any other external portions, have not been included in the electrical specifications  
 System Weight 372 Shipping Weight 412, weights may vary depending on options

- ARI/ISO 13256-2 - Ground Loop Heat Pump
- ARI/ISO 13256-2 - Ground Loop Heat Pump
- ARI/ISO 13256-2 - Ground Water Heat Pump
- ARI/ISO 13256-2 - Ground Water Heat Pump
- ARI/ISO 13256-2 - Water Loop Heat Pump
- ARI/ISO 13256-2 - Water Loop Heat Pump
- ARI 550 - Chiller Rating Points
- ARI 550 - Chiller Rating Points
- Ice Making Rating Points
- Ice Making Rating Points



Model GF1A-120WW-4


Notes to Cabinet Sizing & Physical Characteristics...  
 System sizing and weights may vary, if optional alternate heat exchangers are specified.

System Footprint  
 28.5" (724mm) X 28.5" (724mm)

Fluid Connections  
 A= 1.25" CSF - Loop In  
 B= 1.25" CSF - Loop Out  
 C= 1.25" CSF - Warm/Chilled Fluid In  
 D= 1.25" CSF - Heated/Chilled Fluid Out  
 NOTE: All water connections come standard with copper sweat fitting (CSF) but optional fipnt fittings can installed, upon request.



Model GF2A-120WW ( 240 Nominal )



Model GF3A-120WW ( 360 Nominal )

## GF1-120WW - Fluid-to-Fluid heat pump / chiller

all rights reserved©2006 geoflex systems inc.  
 Geoflex reserves copyrights to all information as listed herein and to change or alter these specifications, without notice.



Unit 3 - 10 Tecumseh Ave., West  
 London, Ontario N6J 1K6  
 P: 519.488.1653 F:519.913.1259  
 E: plant@geoflexsystems.com  
 W: www.geoflexsystems.com